



宁波甬华树脂有限公司

NINGBO YONGHUA RESIN CO.,LTD

Add:No.555 Fengming Road,Ningbo Petrochemical Zone,Ningbo,China.315000

Tel:0086-574-86680024 Fax:0086-574-86680088

www.hh-sh.com Email:amy@hh-sh.com

TECHNICAL DATA SHEET

C5 PETROLEUM RESIN YH-1288™

DESCRIPTION

C5 PETROLEUM RESIN YH-1288™ is suitable for hot melting adhesive,(including quick packaging adhesives,booking adhesives,wood adhesives and glue sticks.ect).They have excellent compatibility with SIS,SBS,EVA,Natural Rubber and many kindks of synthetic rubbers.They provide enchance performance in Hot Melt Adhesive applications, also can used in Road Marking Paints.

PERFORMANCE PROPERTIES

Properties	Typical Value	Test Method
Apperance	Yellowish transparent granule	VISUAL TEST
Softening Point(Ring& Ball,C)	96-104	ASTM E28
Color (Ga#)	4Max	ASTM D1544
Bromine Value (Br g/100g)	25 Max	ASTM D1158
Melt viscosity(200C,cps)	250Max	ASTM D1158
Ash (%)	0.05 Max	ASTM 5040

PACKING,STORING, TANSPORTING:

Granules in multi-ply HDPE inner bags of 25kgs net weight, 500KG bag also viable. To be stored in cool and dry area and keep away from heat and flame.

The information given above is based on our experience and laboratory test. It is given without warranty.

The customer must make his own trials to ensure that glue meets his requirements.

