

**SHANGHAI TITANOS INDUSTRY CO., LTD.**

Rm 2101.No. 915, Zhenbei Road. Shanghai

200333.P.R OF CHINA.

Tel : (86) 2132513559EXT:8023

Fax : (86) 2132513556

Email : lmq@titanos.com.cn

Skype: jamesde6

Technical Data Sheet

Version: 1.1

TITANOS R900 Rutile Titanium Dioxide Pigment

Description	R900 is a multipurpose rutile titanium dioxide pigment suitable for both interior and exterior applications.
Applications	It is recommended for evaluation in: <ul style="list-style-type: none">◆ Decorative architectural coatings – interior and exterior◆ Water and solvent based industrial coatings◆ Powder coatings◆ Low VOC/high solids formulations◆ Plastic with higher requirement on brightness and weather durability◆ Solvent based printing ink
Typical Properties	TiO ₂ content %: 94 Alumina: Yes Zirconia: Yes Organic Treatment: Yes Specific Gravity (g/cm ³): 4.1 Oil Absorption (g/100g): ≤ 20 pH value: 6.0 – 8.5 Residue on sieve of 45 μm (m/m): ≤ 0.05%
Classifications	ISO 591: R2 ASTM D-476-00: Type II CAS number: 13463-67-7 Colour Index: 77891 Pigment white 6
Storage	Keep the product un-stacked in dry and closed rooms at normal temperature and air humidity. To achieve best possible results, we recommend storage under the condition stated above and use within 12 months from delivery.
* Typical Properties not to be construed as specifications	

Disclaimer:

The information given in this publication is obtained from sources believed to be reliable and every effort has been made to ensure that the data is correct and not misleading. However, Titanos group of companies accepts no responsibility for any errors, omissions or incorrect information or for any loss or consequential losses.