



恒河材料科技股份有限公司

HENGHE MATERIALS & SCIENCE TECHNOLOG CO.,LTD

Add:No.3511 Yuejintang Road,Ningbo Petrochemical Zone,Ningbo,China.315000

Tel:0086-574-86680024 Fax:0086-574-86680088

www.hh-sh.com Email:amy@hh-sh.com

TECHNICAL DATA SHEET

C5/C9 COPOLYMERIZED HYDROCARBON RESIN HH2-1004™

DESCRIPTION

C5/C9 COPOLYMERIZED HYDROCARBON RESIN HH2-1004™ is light color thermoplastic resin obtained from polymerizing unsaturated aliphatic/aromatic olefins derived from the process of thermal cracking of naphtha, it mainly used for Hot melt Adhesive,PSA, tapes, Rubber articles, and polymeric coatings.

PERFORMANCE PROPERTIES

Properties	Typical Value	Test Method
Apperance	Yellowish transparent granule	VISUAL TEST
Softening Point(Ring& Ball,C)	95~105	ASTM E28
Color (Ga#)	3.1-4.0	ASTM D1544
Gravity@25C	0.96	ASTM D71
Acid Value (KOHmg/g), ≤	0.3	ASTMD 974
Melt viscosity(Brookfield,mPa·s200C) ≤	250	ASTM 5040

PACKING,STORING, TANSPORTING:

Granules in multi-ply HDPE inner bags of 25kgs net weight. To be stored in cool and dry area and keep away from heat and flame.

The information given above is based on our experience and laboratory test. It is given without warranty.

The customer must make his own trials to ensure that glue meets his requirements.

