

Ethylene Propylene Diene Terpolymer

KUMHO POLYCHEM

Product Data Sheet

Product Description	Features
KEP270 is an EPDM rubber with Medium molecular weight distribution, low ethylene , medium ENB contents. It can be used to Heat resistant hose, washing machine hoses, Window seals, various types of automobile parts.	- High Mooney Viscosity - High vulcanization speed - It is possible to load it with high-level of filler retaining the physical properties.

Test items	Sale Specifications	Unit	Test Method
Volatile Matter	Max 0.75	wt %	ASTM D5668
Mooney Viscosity ML(1+4)@125 °C	71.0 ± 6.0	MU	ASTM D1646
Ethylene Contents	56.5 ± 3.5	wt %	ASTM D3900
ENB Contents	4.5 ± 1.0	wt %	ASTM D6047

Other Products Features

Product Form	Bale
Packaging	25 kg/Bag in Mesh Box, LDPE film, 900 kg (25 kg × 36)
Shelf Life	24 months from date of production at room temperature in dry condition, exposure to light has to be avoided
The Others	RoHS Free

Contact Information

Head Office	East Wing, Signature Tower, #100 Cheonggyecheon-ro, Jung-gu, Seoul, Korea 82-2-6961-1114
Plant	613 Sandanjungang-ro, Yeosu, Jeonnam, Korea 82-61-688-2821
Revision Date	01/11/2025
Revision No.	13